

Branch:

Company Name :  Main Number :

Address :  Main Email :

Job Ref :

**All frames must be viewed from outside. All dimensions in mm must include cills, add-ons or couplers. For bay windows provide internal cill sizes and angles.**

Please circle the following, if required on each frame sketched below :

**Cill Option** - No cill | 85mm cill | 150mm cill | 180mm cill | 225mm cill | welded cill

**Frame Extenders** - 15mm | 35mm

**Couplers** - 10mm Ali

**Door Threshold** - 46mm low pvc | 68mm standard | 15mm low ali

**Corner Posts/Poles** - Window Widgets 90 | Window Widgets variable | Bay corner post  
| 120 fixed | 135 fixed | 150 fixed

**Door & French Doors**- open in | open out | master left | master right

**Our Standard Hardware Specification**

**Windows**

- ERA VS1 Shootbolt Central Locking
- ERA Maxim Handle
- YALE Hinge Guards
- YALE Easy Clean Egress Hinge
- Snap-Lok Glass Clips\*

**Doors**

- YALE Multi Point Lock
- Fab & Fix Handle
- YALE 3\* Cylinder
- Mila Pro Secure Hinge
- Snap-Lok Glass Clips



System:	Featured / Bevelled	Energy Rating:	A+ / A / B / C / Not Required
Outerframe:	Slim 46mm / Int 58mm / Large 68mm	Unit:	28mm DGU / 36mm Triple-Glazed Unit (Special bead)
Colour:	Out: _____ In: _____	Warm Edge Spacer:	Black / Grey / White
Handle Colour:	White / Gold / Chrome / Black / Satin Silver / Antique Black (Monkey tail)	Glazed:	Yes / No
		Bead:	Featured / Bevelled / 36mm (Triple-Glazed)
		Trickle Vent position:	Frame / Sash
		Cylinder:	Key / Thumb Turn

**Sketch windows and doors below detailing all required info shown above on each item...**

Standard Dimensions [unless specified]: Transom - 400 / Mullion - 620 / Midrail - 850

Key :  
Toughened = T  
Obscure = OBS  
Restrictor Hinge = RH