

Branch:

Company Name :  Main Number :

Address :  Main Email :

Job Ref :

**All frames must be viewed from outside. All dimensions in mm must include cills, add-ons or couplers. For bay windows provide internal cill sizes and angles.**

Please specify the following if required on each frame sketched below :

- Cill Option** - No cill | 85mm cill | 150mm cill | 180mm cill | 225mm cill | welded cill
- Frame Extenders** - 10mm | 20mm | 50mm
- Couplers** - 2.5mm | 20mm std | 20mm med | 20mm hd | 20mm structural
- Door Threshold** - 77mm pvc rail | 57mm pvc rail | 15mm part M | 30mm ali - no tray | half tray | full tray
- Door & French Doors**- open in | open out | master left | master right

**Key :**  
 Toughened = T  
 Obscure = OBS  
 Restrictor Hinge = RH

System:	Sculptured / Chamfered (white only)	Energy Rating:	A+ / A
Outerframe:	Standard 57mm / Large 77mm	Unit:	28mm Double Glazed Unit / 40mm Triple-Glazed Unit
Reinforcing:	Standard Reinforcing / Full Steel Reinforcing / Bay Reinforcing	Warm Edge Spacer:	Black / Grey / White
Colour:	White / Rosewood / Rosewood on White / Golden Oak / Golden Oak on White / Anthracite Grey / Anthracite Grey on White / White Foil / Cream Foil	Bead:	28mm Sculptured / 28mm Chamfered / 40mm Sculptured
	Cream Foil on White / Ebony Black / Ebony Black on White / Chartwell Green on White / Irish Oak / Agate Grey (7038) on White		Trickle Vent:
	Special Colour: Out: _____ In: _____	Handle Colour:	White / Gold / Chrome / Stain Silver / Black / Flint
		Handle Shape:	Standard / Non Locking / Monkey Tail / Pear Drop

**Sketch windows and doors below detailing all required info shown above on each item...**

Standard Dimensions [unless specified]: Transom - 400 / Mullion - 620 / Midrail - 850