

Account code	Company Name	Phone Number	Email
--------------	--------------	--------------	-------

Please circle what is applicable

Reference -	Project Type -	Replacement	Extension	New build
-------------	----------------	-------------	-----------	-----------

All frames must be viewed from outside.

All dimensions in mm must include cills, add-ons or couplers. For bay windows provide internal cill sizes and angles. Unless otherwise state our standard specification will apply, Please specify transom drop (400mm), mullion split (620mm), Frame extenders & toughened glass on window sketch, draw openers with arrows pointing to hinges

(Please tick): Alitherm 400i [] -Contemporary frame - flat sash - **INTERNALLY GLAZED** - square bead with dummy sashes
 Alitherm 400x [] -Contemporary frame - flat sash - **EXTERNALLY GLAZED** - square bead

Note: The Alitherm 400i glazed system is a 28mm tap in quickglaze bead as standard.

Note: Externally glazed windows and internally beaded triple glazed windows are wedge gasketed as standard.

Please Circle Items Required

Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q	Glass Supply: YES / Unglazed
Part Q Compliant: Y / N 400x Glass locks ^(Q) : Y / N	Glass specification width^(Q): 28mm DGU 28.8mm lam DGU
Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ex (M) & White Int (G)	Triple glazing- Internally glazed only: 40mm TGU 40.8mm lam TGU <u>If unglazed please tick above glass thickness for gasket type.</u> <i>For externally glazed triple glazing use our REAL System 2 windows</i>
Handle Colour: White / Gold / Chrome / Black / Grey Satin Silver / Graphite / Antique Black (Monkey tail)	Standard Thermal Rating: Window Energy Rating A externally glazed and B internally glazed with 28mm Clear, 1.2 Softcoat, Argon, Black W/edge (Q)
Stayguards^(Q): Y / N	Product U value Special Requirements: _____
Trickle Vent Colour: White / Black / Grey / Silver / Grey on white Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm	Astragal bars for 28mm units only - please tick: [] 25mm Flat bar
Drainage: Face / Concealed	

Hinge codes: S=Standard / E=Egress easy / R=Restrictor / RE=Restrictor Egress (TRI R90)

T/V Trickle vents require a 42mm add-on, fixed to the top of the window

Location	Design (viewed outside, please show T/vents and mullion/trans dimensions)	Qty	Sizes (mm) Including Cills & Add-ons	Cill	Hinge		Glass Spec (Tgh, Obs, Lead)	Add-ons 20mm, 42mm		Special Requirements
					S	E		T	B	
			W	None	85	S	E	T	B	
						R	RE	L	R	
			H	150	190 / 225	2700	4000	5000		
			W	None	85	S	E	T	B	
						R	RE	L	R	
			H	150	190 / 225	2700	4000	5000		
			W	None	85	S	E	T	B	
						R	RE	L	R	
			H	150	190 / 225	2700	4000	5000		

Location	Design (viewed outside, please show T/vents and mullion/trans dimensions)	Qty	Sizes (mm) Including Cills & Add-ons	Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add-ons	Special Requirements
			W	None 85	S E R RE		T B	
			H	150 190 / 225	2700 4000 5000		L R	
			W	None 85	S E R RE		T B	
			H	150 190	2700 4000 5000		L R	
			W	None 85	S E R RE		T B	
			H	150 190 / 225	2700 4000 5000		L R	
			W	None 85	S E R RE		T B	
			H	150 190 / 225	2700 4000 5000		L R	
			W	None 85	S E R RE		T B	
			H	150 190 / 225	2700 4000 5000		L R	
			W	None 85	S E R RE		T B	
			H	150 190	2700 4000 5000		L R	
			W	None 85	S E R RE		T B	
			H	150 190 / 225	2700 4000 5000		L R	
			W	None 85	S E R RE		T B	
			H	150 190 / 225	2700 4000 5000		L R	