

Account code	Company Name	Phone Number	Email
--------------	--------------	--------------	-------

Please circle what is applicable

Reference -	Project Type -	Replacement	Extension	New build
-------------	----------------	-------------	-----------	-----------

All dimensions in mm must include cills, add-ons or couplers. All frames must be viewed from outside. For bay windows provide internal cill sizes and angles. Unless otherwise stated our standard specification will apply. Please specify transom drop (400mm), mullion split (620mm), Frame extenders & toughened glass on window sketch, draw openers with arrows pointing to hinges

70mm system with Contemporary frame - flat sash - internally glazed - square bead
Note: The Alitherm 400 system is a 28mm glazing tap in quickglaze bead as standard. Note: When triple glazing is specified wedge gasket is required.

Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q

Part Q Compliant: Y / N
Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ext (M) & White Int (G)
Handle Colour: White / Gold / Chrome / Black / Satin Silver / Grey / Graphite / Antique Black
Hinge Colour: Grey / Black / White
Hinge Guard (Q): Y / N
Cylinder : STD 3* Security Key-Key / 3* Security Thumb Turn
Drainage: Face / Concealed
Please note - low thresholds are drained through the face of the sash only
Restrictors on open out doors: Yes / No
Fixed Sidelights: Externally glazed Internally glazed / dummy sashes
Note: Sidelights are joined to the door with a 20mm flush coupler as standard.

Glass Supply: YES / Unglazed
Glass spec (Q): Double Glazing 28mm 28.8mm lam
Triple Glazing 40mm 40.8mm lam
If unglazed please tick above glass thickness for gasket type.
Triple glazing will require wedge gasket.
Standard Thermal Rating:
Door Energy Rating C with 28mm Cl tgh, 1.2 softcoat, Argon, Black W/edge (Q)
Product U value special requirements: _____
Flat Panel Supply: YES / Unglazed
Astragal bars for 28mm units only - please tick: [] 25mm Flat
Trickle Vent: White / Black / Grey / Silver / Grey on White
Trickle vent widths 2700mm2=300mm, 4000mm2=400mm and 5000mm2=600mm
Standard Threshold ETD410, 61mm excluding cills
Low threshold ETD490, Rebated & Ramp 15/25mm (open in only) RAL
Low threshold ETD492, Rebate only 15/25mm (open out only) RAL
Low threshold ETD495, with optional ramp 15mm (open in & out) SA

Note: Low ali thresholds are not weather rated and therefore not recommended for exposed locations.

Location	Design (viewed outside, please show T/vents, midrail dimensions, master door)	Qty In/Out	Sizes (mm) Including Cills & Add-ons	Cill	Thresh		Glass Spec (Tgh, Obs, Lead)	Add-ons 20mm, 42mm		Special Requirements
					T/V			T	B	
		Qty:	W	None	Std			T		
				85	Low Ali			B		
		In	H	150	2700			L		
		Out		190 / 225	4000			R		
					5000					
		Qty:	W	None	Std			T		
				85	Low Ali			B		
		In	H	150	2700			L		
		Out		190 / 225	4000			R		
					5000					
		Qty:	W	None	Std			T		
				85	Low Ali			B		
		In	H	150	2700			L		
		Out		190 / 225	4000			R		
					5000					