

Account code

Reference -

Г

~

VISOFOLD 1000 SLIM BI-FOLD DOOR



Please circle what is applicable

Phone Number

Email

Company Name

New build

Project Type -Replacement Extension

All frames must be viewed from outside. All dimensions in mm must include cills, add-ons or couplers. For bay windows provide internal cill sizes and angles.Unless otherwise stade our standard specification will apply, Please specify transom drop (400mm), mullion split (620mm), Frame extenders & toughened glass on window sketch, draw openers with arrows pointing to hinges

Please Circle Items Required								
(Q) = Selection may need to be upgraded to meet Part Q								
System :Visofold Slim 1000 quickglaze clip in bead	Trickle Vent: None / White / Black / Grey / Silver / Grey on White Trickle Vent area: 2700 / 4000 / 5000							
Outer frame: STD DV14 (70mm frame) DV17 (82mm frame)	Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm							
	Glass Supply: YES / Unglazed							
Part Q Compliant: Y / N	Glass Spec: Double Glazing 28mm 28.8mm lam							
<b>Colour:</b> White (G) / Grey (7016M) / Black (9005M) /	Triple Glazing 44mm 44.8mm lam							
Dual Grey Ext (M) & White Int (G)	If unglazed please tick glass thickness for gasket type.							
	Note:Triple glazing will require wedge gaskets.							
Master Door Handle: Lever-Lever only (Shootbolt)	Standard Thermal Rating: Door Energy Rating C with 28m Cl tgh,1.2 Softcoat, Argon, Black W/edge (Q)							
Slave Door Handle (if applicable): Lever-Lever / Intermediate	Glass Special Requirements:							
Intermediate pop out Handles: Locking / Non-Locking	Product U value Special Requirements:							
Lever-Lever Handle Colour: White / Black / Chrome	Threshold: [ ] DV14 51.5mm rebated							
Grey / Graphite / Satin Silver / Gold	<ul> <li>DV17 51.5mm (82mm deep)</li> <li>DV171 15mm low threshold open in</li> </ul>							
Intermediate Handle Colour: White / Black / Grey	DV271 15mm low threshold open out							
	[] DV173 20mm low threshold open in and out							
Hinge Colour: White / Black (recommended)	[ ] DV176 integrated cill (175mm) open out only							
DD Dull Handle (on himsel) White / Discle / Crow	Note: integrated cill requires DV17 outer frame (82mm deep frame)							
<b>'D' Pull Handle</b> (on hinge): White / Black / Grey (recommended)	Delivery : ASSEMBLED FLAT PACK							
Nickel Cylinder <sup>(Q)</sup> : STD 3 * Key-Key	*You will need to ensure able bodied people are available to assist with offloading at the delivery address. If this requirement is not met, you will be charged for the redelivery of the product.*							
Magnetic Hold Open Catch: None / White / Black / Grey / Chrome	Note: Low thresholds not weather rated							

Design (viewed from Τ 

Note: Mullion dimensions can vary depending on style. External access is only available on bi-folds which have a 'lead' door.

Location	outside, show master door)	Design (in open position, viewed from above)	Qty	Cill	Sizes (mm) Including Cills & Add-ons		42mm Add-ons (required with t/vents)		Special Requirements
				None	w		Т		
				Integrated		(max 1200mm per sash)	В		
				85 / 150	н		L		
	Open in / Open out			190 / 225		(max 2500mm)	R		
				None	w		Т		
				Integrated		(max 1200mm per sash)	В		
				85 / 150	н		L		
	Open in / Open out			190 / 225		(max 2500mm)	R		
				None	w		т		
				Integrated		(max 1200mm per sash)	В		
				85 / 150	н		L		
	Open in / Open out			190 / 225		(max 2500mm)	R		
									V13