

Account code  Company Name  Phone Number  Email

Please circle what is applicable

Reference -  Project Type - Replacement Extension New build

All frames must be viewed from outside.  
All dimensions in mm must include cills, add-ons or couplers. For bay windows provide internal cill sizes and angles. Unless otherwise state our standard specification will apply, Please specify transom drop (400mm), mullion split (620mm), Frame extenders & toughened glass on window sketch, draw openers with arrows pointing to hinges

**Please Circle Items Required**

**Part Q Compliant:** Y / N  
(If yes, rollers and locks will be upgraded at an additional charge)

**Outer frame:** Standard / Internal upstand

**Colour:** White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ex (M) & White Int (G)

**Wind loading reqd:** 800 pascals (default) or \_\_\_\_\_ pascals or Site postcode for wind load calc \_\_\_\_\_.

**Sliding door on:** inside track (default) / outside track

**Cill:** None / Two Track 190mm / Three Track 235mm

**Interlocking Mullion:** Standard 83mm / Slim 35mm

**Handle Type:** D / Lever-Lever Internal Only / Internal & External

**Handle Colour:** White / Black / Grey / Satin Silver (Note: Chrome n/a)

(Q) = Selection may need to be upgraded to meet Part Q

**Glass Supply:** Glazed / Unglazed

**Glass Spec:** Double Glazing 28mm T 28.8mm Lam  
Triple Glazing 36mm T 36.8mm Lam

**Standard Thermal Rating:**  
Door Energy Rating C with 28mm Cl tgh, 1.2 Softcoat, Argon, Black W/edge

Glass Special Requirements \_\_\_\_\_

**Nickel Cylinder<sup>(Q)</sup>:** STD Key-Key / STD Thumb Turn  
3\* Security Key-Key / 3\* thumb Turn

**Trickle Vent(s) fitted in 42mm add-on:** QTY [     ]

**Trickle Vent Size EA:** None / 2700 / 4000 / 5000

**TV Colour:** White / Black / Grey / Silver / Grey on White

**Deliver:** Assembled \* / Flat pack frame + sashes

\*You will need to ensure able bodied people are available to assist with offloading at the delivery address. If this requirement is not met you will be charged for the redelivery of the product.

**Key Limits**  
Max sash width for 4mm tgh = 1400mm (approx)  
Max sash width for 6mm tgh = 1700mm (approx)  
Max sash height = 2500mm  
Max sash weight = 200kg

**Key Dimensions**  
Std 2 track frame is 99mm / 3 track frame is 165.5mm  
Internal upstand 2 track frame is 116mm / 3 track frame is 182.5mm  
Standard track plaster cover 43mm  
Internal upstand track plaster cover 53mm  
Frame to glass sightline 117.5mm  
Bi-parting mullion sightline 156mm

**Please indicate style by ticking box ('H' indicates handle position)**

Interlocking mullion      Bi-parting mullion

As shown       Reverse

As shown       Reverse

As shown       Reverse

As shown       Reverse

As shown       Reverse

As shown       Reverse

As shown       Reverse

Qty	Sizes (mm) Including Cills & Add-ons	42mm Add-ons (required with t/vents)	Special Requirements
W		T	
		B	
H	(max 2500mm)	L	
		R	
W		T	
		B	
H	(max 2500mm)	L	
		R	

**Note: Viewed externally**